EVOTECH 1040 (SL)
SYNTHETIC BLEND
PASSENGER CAR ENGINE OIL
API SL SAE 10W-40

Recommended for vehicles manufactured from year 2001 to 2004.
EVOTECH 1040 (SL) is the multigrade performance engine oil specially engineered to exceed the latest API SL standards meant for current generation high performance engines, especially those fitted with emission control devices. It is exclusively formulated with premium mineral base fluids and unique environmentally friendly additives system to provide exceptional thermal and oxidation stability that minimizes oil thickening at very high operating temperatures, excellent deposits control and minimized engine wear and tear.

An advances additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness at extended drain intervals.

Meets the SPECIFICATIONS of:

- **API SL**
- **API CF**

TYPICAL PHYSICAL CHARACTERICS

Characteristics	API SL 10W-40
Density @ 15^{O}C, kg/l	0.878
Pour Point, ^{O}C	-33
Flash Point, ^{O}C	224
Kinematic Viscosity, cSt	
@ 40^{O}C	91.7
@ 100^{O}C	14.60
Viscosity Index	128.32
Cold Cranking Visc @-30^{O}C, cP	6440.92
HTHS @ 150^{O}C (cP)	0.878

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.

200 L

4 L

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com