GALLANTEX 1540
HEAVY DUTY ENGINE OIL
API CI-4 SAE 15W-40

GALLANTEX 1540 is advanced **performance SAE 15W-40 multigrade bio-based diesel engine oil** for use in diesel engines in the most severe on-highway and off-highway applications. It is specially engineered for modern, high-output, low-emission engines including those fitted with Exhaust Gas Recirculation (EGR) as well as older high speed turbo charged engines running on low sulphur diesel or conventional high sulphur diesel fuel.

The **bio based base oil** derived from palm oil derivatives has been tested and utilized for the production of this lubricant. **Fully Synthetic Bio based** base oil utilised for this lubricant products reduces harmful carbon and totally eliminate sulphur emission & deposit in the engine.

An advances additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness at extended drain intervals.

PRODUCT NAME : GALLENTEX 1540

Comform to performance requirement of specification:

- **API CI-4**
- **SAE 15W-40**

PRODUCT SPECIFICATION

Characteristics	Test Method	API CI-4 SAE 15W-40
Kinematic Viscosity,mm2/s@ 100^{O}C	ASTM D 7042	15.03
Kinematic Viscosity,mm2/s@ 40^{O}C	ASTM D 7042	113.83
Flash Point, ^{O}C	ASTM D 93	236
Viscosity Index	ASTM D 2270	137
Total Base Number (TBN)	ASTM D 2896	10.37

INTERTEK Report No: ITSPK/LB/4128/2018

209L

18 L

4 L

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com