PRODUCT DATA SHEET

GALLANTEX 2050
ENGINE OIL SAE 20W 50
API CF-4

Recommended for vehicles manufactured from year 1990 to year 1994.
GALLANTEX 2050 is advanced performance SAE 20W-50 **mineral multigrade engine oil** for use in the most severe **high speed naturally aspirated or turbo charged diesel engines.** on-highway and off-highway applications. It is specially engineered for modern, high-output, low-emission engines including those fitted with Exhaust Gas Recirculation (EGR) as well as older high speed turbo charged engines running on low sulphur diesel or conventional high sulphur diesel fuel.

An advances additive system ensures excellent control over , **control over piston deposits, wear and bearing corrosion.** It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness at extended drain intervals**. It is free from defects and contamination**

Meets the SPECIFICATIONS of:
- **API CF-4**
- **API CF**

TYPICAL PHYSICAL CHARACTERICS

Characteristics	Test Method	API CF-4 SAE 20W-50
Flash Point, ^{O}C	ASTM D 92	240
Kinematic Viscosity, @ 40^{O} C, CSt	ASTM D 7042	166
Kinematic Viscosity, @ 100^{O}C, Cst	ASTM D 7042	21.1
Viscosity Index	ASTM D 2270	150

INTERTEK Report No: ITSPK/LB/0706/2019
STRIDE Report No: TB/P1892/096(A)

209 L

18 L

4 L

Produced by:
NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com