HYDEX 68
HYDRAULIC OIL
ISOVG 68 (HF-0)

HYDEX 68 is premium quality anti-wear ISO VG 68 hydraulic fluids designed for use in hydraulic systems in marine engines, industrial and commercial equipment with excellent **anti-wear, anti corrosion and anti rust properties**. They are formulated from premium **semi- synthetic quality petroleum base oil** and **advanced additive** to provide excellent protection against wear and corrosion, **enhanced thermal properties and oxidation stability**, and resistance to rusting and foaming.

Meets the SPECIFICATIONS of:

- **DIN 51524 Part 2**
- **Parker Hannifin France HF-0**
- **Eaton Brochure 03-401-2010**
- **Cincinnati Machine P-69**
- **Cincinnati Machine P-68**
- **Cincinnati Machine P-70**

TYPICAL PHYSICAL CHARACTERICS

Characteristics	TEST METHOD	ISO VISCOSITY GRADE 68
Kinematic Viscosity, cSt@ 40^{O}C	ASTM D 7042	65.54
Kinematic Viscosity, cSt@ 100^{O}C	ASTM D 7042	9.572
Viscosity Index	ASTM D 2270	135
Pour Point, ^{O}C	ASTM D 97	-54
Flash Point, ^{O}C	ASTM D 92	268

209 L

18 L

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com