# MOTORIX 2T
## 2T MOTOR CYCLE ENGINE OIL
## API TC / JASO FD

**Recommended for vehicles which requires the specifications of JASO FD**

**MOTORIX 2T** is complex blend of oil and additives directly address the heat, pressure and friction of race-engineered engines. These engines operate on the edge, yet engine reliability is critical. **MOTORIX 2T** does an outstanding job protecting high-performance engines. It adds durability that professional racing teams depend on and delivers confidence so engines can be pushed to the limit. Excellent lubricity and Film Strength High-performance and race-designed two-stroke engines operate under severe conditions. They are modified for higher compression ratios, higher rpm and leaner combustion, all of which increase heat and pressure. High heat can quickly burn off light oil and cause rapid piston expansion, decreasing piston-to-cylinder wall clearances and increasing the likelihood of piston scuffing and seizure. High pressure can exceed the film strength of low-viscosity oil, which promotes crankshaft bearing wear and pitting. **MOTORIX 2T** is purpose-built for outstanding film strength and lubricity. It is engineered with carefully selected, higher-viscosity base oil to withstand the high heat and pressure common to high-performance and racing applications. **MOTORIX 2T's** anti-friction chemistry is race-proven to provide an extra measure of protection against piston scuffing and bearing wear.

**Meets the SPECIFICATIONS of:**

- **ISO-L-EGD**
- **JASO FD**

## TYPICAL PHYSICAL CHARACTERISTICS

| Characteristics | JASO FD |
|---|---|
| Density @ 15$^{O}$C, kg/l | 0.872 |
| Pour Point, $^{O}$C | -33 |
| Flash Point, $^{O}$C | > 68 |
| Kinematic Viscosity, cSt | |
| @ 100$^{O}$C | 13.24 |
| Viscosity Index | 128 |

*The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.*

*PACKING AVAILABLE IN VARIOUS SIZES*

| 209L | | 20L | | 18L | | 7L | | 5L | | 4L | | 1L | √ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

*Product shelf life is 3 years from the date of acceptance.*

**Produced by:**

**NANOC VENTURES SDN. BHD. (734618-A)**
**Office & Factory:**
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com