MOTORIX PREMIUM 1040

SEMI SYNTHETIC
4T MOTOR CYCLE ENGINE OIL
API SN SAE 10W-40 JASO MA2

Recommended for vehicles manufactured from year 2004 onwards With API Compliance.
MOTORIX PREMIUM 1040 is the next generation ultimate performance synthetic blend multigrade engine oil specially engineered to exceed the API SN standards meant for current and future generation high performance motorcycle engines, It is exclusively formulated with premium semi-synthetic base fluids and unique environmentally friendly additives system to provide exceptional thermal and oxidation stability that minimizes oil thickening at very high operating temperatures, excellent deposits control and minimized engine wear and tear.

An advances additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness.

Meets the SPECIFICATIONS of:
- **API SN**
- **JASO MA2**

TYPICAL PHYSICAL CHARACTERICS

Characteristics	API SN SAE 10W-40
Density @ 15^{O}C, kg/l	0.857
Pour Point, ^{O}C	-32
Flash Point, ^{O}C	223
Kinematic Viscosity, cSt	
@ 40^{O}C	102.492
@ 100^{O}C	14.4
Viscosity Index	149.87
Cold Cranking Visc @-30^{O}C, cP	6500
HTHS @ 150^{O}C (cP)	3.918

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.

PACKING AVAILABLE IN VARIOUS SIZES

209L		20L		18L		7L		5L		4L	√	1L	√

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com