MOTORIX PREMIUM 1040

SEMI SYNTHETIC
4T SCOOTER ENGINE OIL
API SN SAE 10W-40 JASO MB

Recommended for Scooters manufactured from year 2011 onwards With API Compliance.

MOTORIX PREMIUM 1040 is a high quality lubricant suitable for use in air-cooled two-stroke gasoline scooter engines operating under severe conditions. It consists of highly refined base ingredients fortified with carefully selected additives to ensure the protection and engine cleanliness. Offers great lubrication that protects against piston abrasion and premature wear of engine parts. Great miscibility with gasoline ensures a homogeneous mixture even at low ambient temperatures.

An advances additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness.

Meets the SPECIFICATIONS of:

- **API SN**
- **JASO MB**

TYPICAL PHYSICAL CHARACTERICS

Characteristics	API SN SAE 10W-40
Density @ 15^{O}C, kg/l	0.857
Pour Point, ^{O}C	-31
Flash Point, ^{O}C	221
Kinematic Viscosity, cSt	
@ 40^{O}C	103
@ 100^{O}C	14.
Viscosity Index	137.7
Cold Cranking Visc @-30^{O}C, cP	6500
HTHS @ 150^{O}C (cP)	3.918

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.

PACKING AVAILABLE IN VARIOUS SIZES

209L		20L		18L		7L		5L		4L	√	1L	√

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com