MOTORIX SUPREME 2050
FULLY SYNTHETIC
4T MOTOR CYCLE ENGINE OIL
API SN SAE 20W-50 JASO MA-2

Recommended for vehicles manufactured from year 2004 onwards With API Compliance.
MOTORIX SUPREME 2050 is the next generation ultimate performance fully synthetic multigrade engine oil specially engineered to exceed the API SM standards meant for current and future generation high performance motorcycle engines, It is exclusively formulated with premium synthetic base fluids and unique environmentally friendly additives system to provide exceptional thermal and oxidation stability that minimizes oil thickening at very high operating temperatures, excellent deposits control and minimized engine wear and tear.

An advances additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness.

Comform to performance requirement of:

- **API SN**
- **JASO MA2**

TYPICAL PHYSICAL CHARACTERISTICS

Characteristics	API SM SAE 20W50
Density @ 15^{O}C, kg/l	0.868
Pour Point, ^{O}C	-32
Flash Point, ^{O}C	223
Kinematic Viscosity, cSt	
@ 40^{O}C	104.21
@ 100^{O}C	18.72
Viscosity Index	160.65
Cold Cranking Visc @-30^{O}C, cP	1337.67
HTHS @ 150^{O}C (cP)	4.03

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.

4 L

1 L

Produced by:

NANOC VENTURES SDN. BHD. (734618-A)
Office & Factory:
No.3, Jalan SR 7/11, Taman Serdang Raya, 43300 Seri Kembangan, Selangor
Tel: 03-89579920 Fax: 03-89599920 Email: info@nanocventures.com